



GE L3-12-D Linear Array

Center Frequency: 6.5 MHz **Bandwidth:** 85%
Number of elements: 256 **Pitch:** 0.20mm
Elevation Focus: 22 mm **Elevation aperture:** 5.0 mm
MUX: Yes **Compatibility:** Vantage 256, 128, 64LE



GE 4C-D Curved Linear Array

Center Frequency: 3.2 MHz **Bandwidth:** 70%
Number of elements: 128 **Pitch:** 0.478mm
Elevation Focus: 67 mm **Elevation aperture:** 13 mm
Radius of Curvature: 60.0 **Compatibility:** Vantage 256, 128, 64LE



GE C1-6-D Curved Linear Array

Center Frequency: 3.4 MHz **Bandwidth:** 95%
Number of Elements: 192 **Pitch:** 0.350mm
Elevation Focus: 66 mm **Elevation Aperture:** 11.5 mm
Radius of Curvature: 56.8 **Compatibility:** Vantage 256



GE IC5-9-D Intracavitary Curved Linear Array

Center Frequency: 5.8 MHz **Bandwidth:** 75%
Number of elements: 192 **Pitch:** 0.138mm
Elevation Focus: 35 mm **Elevation aperture:** 6.0 mm
Radius of Curvature: 10.1mm **Compatibility:** Vantage 256



GE M5Sc-D Phased Array

Center Frequency: 2.8 MHz **Bandwidth:** 90%
Number of elements: 80 x 3 **Pitch:** 0.23 mm
Elevation Focus: 77 mm **Elevation aperture:** 13.0 mm
Compatibility: Vantage 256



9L-D

Center Frequency: 5.3 MHz **Bandwidth:** 75%
Number of elements: 192 **Pitch:** 0.23 mm
Elevation Focus: 28 mm **Elevation aperture:** 6.0 mm
MUX: No **Compatibility:** Vantage 256

